



## 400400G 1/2" Dr. Super Duty Air Impact Wrench

### Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	380 ft. lbs. / 516 Nm
Free Speed	7,000 rpm
Overall Length	7.5 in. / 190 mm
Avg. Air Consumption	4.0 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Pin Clutch

 2700 g

 8 pcs / 24.1 Kgs / 1.32 CUFT


**380**  
FT.-LBS.




## 400401 1/2" Dr. Super Duty Lightweight Mini Air Impact Wrench

### Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	400 ft. lbs. / 542 Nm
Free Speed	11,000 rpm
Overall Length	5.6 in / 142 mm
Avg. Air Consumption	3.2 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

 1600 g

 10 pcs / 17 Kgs / 0.7 CUFT

**400**  
FT.-LBS.


**1.6**  
KGS  
Lightweight




## 400402 1/2" Dr. Super Duty Lightweight Mini Long Anvil Air Impact Wrench

### Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	400 ft. lbs. / 542 Nm
Free Speed	11,000 rpm
Overall Length	7.6 in / 192 mm
Avg. Air Consumption	3.2 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

 1700 g

 10 pcs / 19 Kgs / 0.75 CUFT

**400**  
FT.-LBS.

**1.7**  
KGS  
Lightweight



### Caution

- Proper use will extend the usage period 2 to 3 times.
- After oiling, remember to first pull the trigger for no longer than 2 seconds. Otherwise, it will seriously affect performance as well as shorten the life of the tool itself.
- Please add 2-3cc #R32 oil to grease the motor everyday before use.
- Please add 20-30cc #R40 oil to grease the impact set every 3 to 6 months.
- Do not drive or remove screws that would require the use of the unit for more than 5 seconds at one time. If the screws are rusty or too tight, please use other method to remove them.
- Please locate dust cover after using to extend the usage period.