

400511 1/2" Dr. Super Duty Lightweight Mini Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	500 ft. lbs. / 678 Nm
Free Speed	11,000 rpm
Overall Length	3.9 in. / 99 mm
Avg. Air Consumption	3.2 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Jumbo Hammer

1340 g

10 pcs / 16 Kgs / 0.9 CUFT

500
FT.-LBS.

1.3
KGS
Lightweight



400500 1/2" Dr. Super Duty Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	500 ft. lbs. / 678 Nm
Free Speed	7,000 rpm
Overall Length	7.6 in. / 190 mm
Avg. Air Consumption	5.4 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

2900 g

6 pcs / 19.8 Kgs / 0.98 CUFT

500
FT.-LBS.



400502 1/2" Dr. Super Duty Long Anvil Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	500 ft. lbs. / 678 Nm
Free Speed	7,000 rpm
Overall Length	9.6 in. / 245 mm
Avg. Air Consumption	5.4 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

3000 g

2 pcs / 7 Kgs / 0.4 CUFT

500
FT.-LBS.



Caution

- Proper use will extend the usage period 2 to 3 times.
- After oiling, remember to first pull the trigger for no longer than 2 seconds. Otherwise, it will seriously affect performance as well as shorten the life of the tool itself.
- Please add 2-3cc #R32 oil to grease the motor everyday before use.
- Please add 20-30cc #R40 oil to grease the impact set every 3 to 6 months.
- Do not drive or remove screws that would require the use of the unit for more than 5 seconds at one time. If the screws are rusty or too tight, please use other method to remove them.
- Please locate dust cover after using to extend the usage period.