

4K0950 1/2" Dr. Ultra Duty Air Impact Wrench**Specifications:**

Air Pressure	90 psig / 620 kpa
Max. Torque	700 ft. lbs. / 950 Nm
Free Speed	8,000 rpm
Overall Length	7.6 in / 193 mm
Avg. Air Consumption	4.4 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

 2100 g

 8 pcs / 19.5 Kgs / 1.3 CUFT
**700
FT.-LBS.****4K0952 1/2" Dr. Ultra Duty Long Anvil Air Impact Wrench****Specifications:**

Air Pressure	90 psig / 620 kpa
Max. Torque	700 ft. lbs. / 950 Nm
Free Speed	8,000 rpm
Overall Length	9.6 in / 243 mm
Avg. Air Consumption	4.4 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

 2200 g

 8 pcs / 21 Kgs / 1.8 CUFT
**700
FT.-LBS.****400800 1/2" Dr. Ultra Duty Air Impact Wrench****Specifications:**

Air Pressure	90 psig / 620 kpa
Max. Torque	800 ft. lbs. / 1,085 Nm
Free Speed	7,500 rpm
Overall Length	6.5 in. / 165 mm
Avg. Air Consumption	4.5 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

 2500 g

 6 pcs / 17 Kgs / 0.7 CUFT
**800
FT.-LBS.****400802 1/2" Dr. Ultra Duty Long Anvil Air Impact Wrench****Specifications:**

Air Pressure	90 psig / 620 kpa
Max. Torque	800 ft. lbs. / 1,085 Nm
Free Speed	7,500 rpm
Overall Length	8.5 in. / 215 mm
Avg. Air Consumption	4.5 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

 2600 g

 6 pcs / 18 Kgs / 0.8 CUFT
**800
FT.-LBS.**