

600750 3/4" Dr. Heavy Duty Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	750 ft. lbs. / 1,016 Nm
Free Speed	6,500 rpm
Overall Length	9 in. / 230 mm
Avg. Air Consumption	7.0 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

4550 g

4 pcs / 21 Kgs / 0.97 CUFT

750
FT.-LBS.



600756 3/4" Dr. Heavy Duty Long Anvil Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	750 ft. lbs. / 1,016 Nm
Free Speed	6,500 rpm
Overall Length	14 in. / 355 mm
Avg. Air Consumption	7.0 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

5200 g

2 pcs / 11.5 Kgs / 0.7 CUFT

750
FT.-LBS.



600850 3/4" Dr. Super Duty Lightweight Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	850 ft. lbs. / 1,152 Nm
Free Speed	7,500 rpm
Overall Length	6.7 in. / 170 mm
Avg. Air Consumption	4.5 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

2500 g

6 pcs / 17 Kgs / 0.7 CUFT

850
FT.-LBS.

2.5
KGS
Lightweight



600856 3/4" Dr. Super Duty Lightweight Long Anvil Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	850 ft. lbs. / 1,152 Nm
Free Speed	7,500 rpm
Overall Length	12.8 in. / 325 mm
Avg. Air Consumption	4.5 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

3100 g

6 pcs / 20 Kgs / 1.4 CUFT

850
FT.-LBS.

3.1
KGS
Lightweight

