

600900G 3/4" Dr. Super Duty Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	900 ft. lbs. / 1,220 Nm
Free Speed	4,600 rpm
Overall Length	9.6 in. / 245 mm
Avg. Air Consumption	7.5 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Pin Clutch

4800 g

4 pcs / 21 Kgs / 1.2 CUFT

900
FT.-LBS.



601100 3/4" Dr. Super Duty Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	1,100 ft. lbs. / 1,491 Nm
Free Speed	6,000 rpm
Overall Length	8.2 in. / 208 mm
Avg. Air Consumption	6.0 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

4100 g

4 pcs / 18.6 Kgs / 0.85 CUFT

1100
FT.-LBS.



601106 3/4" Dr. Super Duty Long Anvil Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	1,100 ft. lbs. / 1,491 Nm
Free Speed	6,000 rpm
Overall Length	14.2 in. / 360 mm
Avg. Air Consumption	6.0 cfm
Air Inlet	1/4 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

4700 g

4 pcs / 21.5 Kgs / 1.3 CUFT

1100
FT.-LBS.



6K1490 3/4" Dr. Ultra Duty Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	1,100 ft. lbs. / 1,491 Nm
Free Speed	5,500 rpm
Overall Length	8.6 in. / 220 mm
Avg. Air Consumption	9.5 cfm
Air Inlet	3/8 in.
Minimum Hose Size	1/2 in. / 12.7 mm
Machine Design	Twim Hammer

5600 g

4 pcs / 24.5 Kgs / 1.24 CUFT

1100
FT.-LBS.

