

801512 1" Dr. Super Duty Lightweight Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	1,500 ft. lbs. / 2,033 Nm
Free Speed	4,500 rpm
Overall Length	8.8 in. / 222 mm
Avg. Air Consumption	9.0 cfm
Air Inlet	3/8 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

5100 g

4 pcs / 22.5 Kgs / 0.85 CUFT

1500
FT.-LBS.

5.1
KGS
Lightweight



801518 1" Dr. Super Duty Lightweight Long Anvil Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	1,500 ft. lbs. / 2,033 Nm
Free Speed	4,500 rpm
Overall Length	14.8 in. / 375 mm
Avg. Air Consumption	9.0 cfm
Air Inlet	3/8 in.
Minimum Hose Size	3/8 in. / 10 mm
Machine Design	Twin Hammer

6100 g

4 pcs / 27 Kgs / 1.3 CUFT

1500
FT.-LBS.

6.1
KGS
Lightweight



801500 1" Dr. Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	1,500 ft. lbs. / 2,033 Nm
Free Speed	4,000 rpm
Overall Length	15.1 in. / 385 mm
Avg. Air Consumption	13.2 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer

9600 g

1 pc / 11.6 Kgs / 0.97 CUFT

1500
FT.-LBS.



801506 1" Dr. Long Anvil Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	1,500 ft. lbs. / 2,033 Nm
Free Speed	4,000 rpm
Overall Length	20.6 in. / 525 mm
Avg. Air Consumption	13.2 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer

11 kg

1 pc / 13 Kgs / 0.97 CUFT

1500
FT.-LBS.

