

801800 1" Dr. Super Duty Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	1,800 ft. lbs. / 2,439 Nm
Free Speed	4,000 rpm
Overall Length	14.5 in. / 370 mm
Avg. Air Consumption	13.2 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer

10.5 kg

2 pcs / 25 Kgs / 1.8 CUFT

1800
FT.-LBS.



801806 1" Dr. Super Duty Long Anvil Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	1,800 ft. lbs. / 2,439 Nm
Free Speed	4,000 rpm
Overall Length	21.6 in. / 550 mm
Avg. Air Consumption	13.2 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer

12 Kg

1 pc / 14 Kgs / 0.97 CUFT

1800
FT.-LBS.



802000 1" Dr. Super Duty Lightweight Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	2,000 ft. lbs. / 2,712 Nm
Free Speed	5,000 rpm
Overall Length	13.6 in. / 345 mm
Avg. Air Consumption	9.0 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer

7300 g

2 pcs / 17.5 Kgs / 1.3 CUFT

2000
FT.-LBS.

7.3
KGS
Lightweight



802006 1" Dr. Super Duty Lightweight Long Anvi Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	2,000 ft. lbs. / 2,712 Nm
Free Speed	5,000 rpm
Overall Length	19.1 in. / 485 mm
Avg. Air Consumption	9.0 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer

8300 g

2 pcs / 19.5 Kgs / 1.3 CUFT

2000
FT.-LBS.

8.3
KGS
Lightweight

