

943000 1-1/2" Dr. Super Duty Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	3,000 ft. lbs. / 4,068 Nm
Free Speed	3,700 rpm
Overall Length	19.3 in. / 490 mm
Avg. Air Consumption	14.7 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer

 14.9 Kg

 1 pc / 17.7 Kgs / 1.32 CUFT

3000
FT.-LBS.


1½

943008 1-1/2" Dr. Super Duty Long Anvil Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	3,000 ft. lbs. / 4,068 Nm
Free Speed	3,700 rpm
Overall Length	27.2 in. / 690 mm
Avg. Air Consumption	14.7 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer

 17.2 Kg

 1 pc / 20 Kgs / 1.32 CUFT

3000
FT.-LBS.


1½

501800 #5 Spline Dr. Super Duty Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	1,800 ft. lbs. / 2,439 Nm
Free Speed	4,000 rpm
Overall Length	14.5 in. / 370 mm
Avg. Air Consumption	13.2 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer

 10.5 Kg

 1 pc / 12.5 Kgs / 0.97 CUFT

1800
FT.-LBS.


#5

501806 #5 Spline Dr. Super Duty Long Anvil Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	1,800 ft. lbs. / 2,439 Nm
Free Speed	4,000 rpm
Overall Length	21.6 in. / 550 mm
Avg. Air Consumption	13.2 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer

 12.5 Kg

 1 pc / 14.5 Kgs / 0.97 CUFT

1800
FT.-LBS.


#5