


1 1/2"

Air Impact Wrenches

9K3390 1-1/2" Dr. Ultra Duty Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	2,500 ft. lbs. / 3,390 Nm
Free Speed	3,000 rpm
Overall Length	18 in. / 455 mm
Avg. Air Consumption	14.5 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer


 16.3 kg


 1 pc / 18.8 Kgs / 1.5 CUFT
**2500
FT.-LBS.**

9K3398 1-1/2" Dr. Ultra Duty Long Anvil Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	2,500 ft. lbs. / 3,390 Nm
Free Speed	3,000 rpm
Overall Length	23.8 in. / 605 mm
Avg. Air Consumption	14.5 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer


 18.7 kg

 1 pc / 21.2 Kgs / 1.5 CUFT
**2500
FT.-LBS.**

9K4070 1-1/2" Dr. Ultra Duty Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	3,000 ft. lbs. / 4,070 Nm
Free Speed	3,000 rpm
Overall Length	18.5 in. / 470 mm
Avg. Air Consumption	16 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer

 17 kg

 1 pc / 19.5 Kgs / 1.5 CUFT
**3000
FT.-LBS.**

9K4078 1-1/2" Dr. Ultra Duty Long Anvil Air Impact Wrench

Specifications:

Air Pressure	90 psig / 620 kpa
Max. Torque	3,000 ft. lbs. / 4,070 Nm
Free Speed	3,000 rpm
Overall Length	25.6 in. / 650 mm
Avg. Air Consumption	16 cfm
Air Inlet	1/2 in.
Minimum Hose Size	3/4 in. / 19 mm
Machine Design	Twin Hammer

 20 kg

 1 pc / 22.5 Kgs / 1.5 CUFT
**3000
FT.-LBS.**