



SI-1170

DRIVERS

IMPACT DRIVERS
SCREW DRIVERS

DRIVERS Impact Drivers

SI-1052

Impact Driver

- 6mm capacity straight grip impact driver
- Have regulator built-in
- Compact body design for reduce weight and easy operation




Shank Size in.(mm)	1/4(6.35)
Max Torque Nm/(ft-lb)	70/(51.6)
Working Torque Nm/(ft-lb)	0.65/(0.44)
Bolt Cap mm/(in.)	5.63(1/8)
Free Speed r.p.m.	13,000
Weight kg/(lb)	0.56(1.23)
Noise Level dBA/(power)	90/(101)
Vibration a/k m/s ²	9.3/1.4
Max Air Consumption CFM/(L/S)	13.8/(6.5)
Avg Air Consumption CFM/(L/S)	2.3/(1.1)
Air Inlet Size in.	1/4

SI-1062

Impact Driver

- More powerful than SI-1052
- Built-in regulator
- Compact body design for reduce weight and easy operation



Shank Size in.(mm)	1/4(6.35)
Max Torque Nm/(ft-lb)	80/(70.1)
Working Torque Nm/(ft-lb)	0.70/(0.52)
Bolt Cap mm/(in.)	6/(1/4)
Free Speed r.p.m.	10,000
Weight kg/(lb)	0.79/(1.74)
Noise Level dBA/(power)	87/(98)
Vibration a/k m/s ²	9.8/1.4
Max Air Consumption CFM/(L/S)	16.8/(7.9)
Avg Air Consumption CFM/(L/S)	2.8/(1.3)
Air Inlet Size in.	1/4

SI-1060

Impact Driver

- 6mm capacity straight grip impact driver
- Compact, lightweight, ergonomic design for easy operation
- General use



Shank Size in.(mm)	1/4(6.35)
Max Torque Nm/(ft-lb)	65/(47.9)
Working Torque Nm/(ft-lb)	0.53/(0.37)
Bolt Cap mm/(in.)	6/(1/4)
Free Speed r.p.m.	11,000
Weight kg/(lb)	0.87/(1.92)
Noise Level dBA/(power)	89/(100)
Vibration a/k m/s ²	10.9/2.8
Max Air Consumption CFM/(L/S)	17.4/(8.2)
Avg Air Consumption CFM/(L/S)	2.9/(1.4)
Air Inlet Size in.	1/4

SI-1065

Impact Driver

- 6mm capacity pistol grip impact driver
- General use
- Ergonomic pistol grip for easy operation



Shank Size in.(mm)	1/4(6.35)
Max Torque Nm/(ft-lb)	65/(47.9)
Working Torque Nm/(ft-lb)	0.45/(0.33)
Bolt Cap mm/(in.)	6/(1/4)
Free Speed r.p.m.	11,000
Weight kg/(lb)	0.98/(2.16)
Noise Level dBA/(power)	88/(99)
Vibration a/k m/s ²	6.9/2.0
Max Air Consumption CFM/(L/S)	20.4/(9.6)
Avg Air Consumption CFM/(L/S)	3.4/(1.6)
Air Inlet Size in.	1/4

SI-1356D

Impact Driver

- 8mm capacity pistol grip impact driver
- Double hammer mechanism



Shank Size in.(mm)	1/4(6.35)
Max Torque Nm/(ft-lb)	55/(40.6)
Working Torque Nm/(ft-lb)	0.45/(0.33)
Bolt Cap mm/(in.)	6.5(1/8)
Free Speed r.p.m.	9,000
Weight kg/(lb)	1.22/(2.69)
Noise Level dBA/(power)	87/(98)
Vibration a/k m/s ²	6.6/1.1
Max Air Consumption CFM/(L/S)	16.2/(7.6)
Avg Air Consumption CFM/(L/S)	2.7/(1.3)
Air Inlet Size in.	1/4

SI-1365D

Impact Driver

- 8mm capacity pistol grip impact driver
- Industrial use



Shank Size in.(mm)	1/4(6.35)
Max Torque Nm/(ft-lb)	70/(51.6)
Working Torque Nm/(ft-lb)	0.60/(0.44)
Bolt Cap mm/(in.)	8/(5/16)
Free Speed r.p.m.	8,000
Weight kg/(lb)	1.32/(2.92)
Noise Level dBA/(power)	84/(95)
Vibration a/k m/s ²	7.6/2.6
Max Air Consumption CFM/(L/S)	19.8/(9.3)
Avg Air Consumption CFM/(L/S)	3.3/(1.6)
Air Inlet Size in.	1/4