



SI-1052

Impact Driver

- 6mm capacity straight grip impact driver
- Have regulator built-in
- Compact body design for reduce weight and easy operation





Shank Size in./(mm)	1/4/(6,35)
Max Torque Nm/(ft-lb)	70/(51,6)
Working Torque Nm/(ft-lb)	0-60/(0-44)
Bolt Cap mm/(in.)	5/(3/16)
Free Speed r/min	13,000
Weight kg/(lb)	0,56/(1,23)
Noise Level dBA/(power)	90/(101)
Vibration a/k m/s ²	9,3/1,4
Max Air Consumption CFM/(L/S)	13,8/(6,5)
Avg Air Consumption CFM/(L/S)	2,3/(1,1)
Air Inlet Size in.	1/4

SI-1062

Impact Driver

- More powerful than SI-1052
- Built-in regulator
- Compact body design for reduce weight and easy operation



Shank Size in./(mm)	1/4/(6,35)
Max Torque Nm/(ft-lb)	80/(70,1)
Working Torque Nm/(ft-lb)	0-70/(0-52)
Bolt Cap mm/(in.)	6/(1/4)
Free Speed r/min	10,000
Weight kg/(lb)	0,79/(1,74)
Noise Level dBA/(power)	87/(98)
Vibration a/k m/s ²	9,8/1,4
Max Air Consumption CFM/(L/S)	16,8/(7,9)
Avg Air Consumption CFM/(L/S)	2,8/(1,3)
Air Inlet Size in.	1/4

SI-1060

Impact Driver

- 6mm capacity straight grip impact driver
- Compact, lightweight, ergonomic design for easy operation
- General use



Shank Size in./(mm)	1/4/(6,35)
Max Torque Nm/(ft-lb)	65/(47,9)
Working Torque Nm/(ft-lb)	0-50/(0-37)
Bolt Cap mm/(in.)	6/(1/4)
Free Speed r/min	11,000
Weight kg/(lb)	0,87/(1,92)
Noise Level dBA/(power)	89/(100)
Vibration a/k m/s ²	10,8/2,8
Max Air Consumption CFM/(L/S)	17,4/(8,2)
Avg Air Consumption CFM/(L/S)	2,9/(1,4)
Air Inlet Size in.	1/4

SI-1065

Impact Driver

- 6mm capacity pistol grip impact driver
- General use
- Ergonomic pistol grip for easy operation




Shank Size in./(mm)	1/4/(6,35)
Max Torque Nm/(ft-lb)	85/(147,9)
Working Torque Nm/(ft-lb)	0-45/(0-33)
Bolt Cap mm/(in.)	6/(1/4)
Free Speed r/min	11,000
Weight kg/(lb)	0,58/(2,16)
Noise Level dBA/(power)	88/(99)
Vibration a/k m/s ²	6,9/2,0
Max Air Consumption CFM/(L/S)	20,4/(9,6)
Avg Air Consumption CFM/(L/S)	3,4/(1,6)
Air Inlet Size in.	1/4

SI-1356D

Impact Driver

- 8mm capacity pistol grip impact driver
- Double hammer mechanism




Shank Size in./(mm)	1/4/(6,35)
Max Torque Nm/(ft-lb)	55/(40,6)
Working Torque Nm/(ft-lb)	0-45/(0-33)
Bolt Cap mm/(in.)	8/(5/16)
Free Speed r/min	9,000
Weight kg/(lb)	1,22/(2,69)
Noise Level dBA/(power)	87/(98)
Vibration a/k m/s ²	6,6/1,1
Max Air Consumption CFM/(L/S)	16,2/(7,6)
Avg Air Consumption CFM/(L/S)	2,7/(1,3)
Air Inlet Size in.	1/4

SI-1365D

Impact Driver

- 8mm capacity pistol grip impact driver
- Industrial use



Shank Size in./(mm)	1/4/(6,35)
Max Torque Nm/(ft-lb)	70/(51,6)
Working Torque Nm/(ft-lb)	0-60/(0-44)
Bolt Cap mm/(in.)	8/(5/16)
Free Speed r/min	8,000
Weight kg/(lb)	1,32/(2,92)
Noise Level dBA/(power)	84/(95)
Vibration a/k m/s ²	7,6/2,6
Max Air Consumption CFM/(L/S)	19,8/(9,3)
Avg Air Consumption CFM/(L/S)	3,3/(1,6)
Air Inlet Size in.	1/4

DRIVERS

IMPACT DRIVERS
SCREW DRIVERS

SI-1170

IMPACT WRENCHES
DRIVERS
RATCHET WRENCHES
SCREWDRIVERS
PUSHERS
GRABBERS
SPRINTERS
CUTTING TOOLS
OTHERS
INDUSTRIAL TOOLS
ACCESSORIES
SOUND VIBRATION
MAINTENANCE CHECK
QUALITY