

RATCHET WRENCHES

1/4" Ratchet Wrenches · 3/8" Ratchet Wrenches


RATCHET WRENCHES

1/2" Ratchet Wrenches · 1/4" Ratchet Wrench · 3/8" Ratchet Wrenches

SI-1107B

1/4" Ratchet Wrench

- Super small ratchet wrench with 1/4"sq. anvil
- Smaller than SI-1200B & SI-1205B




Shank Size in./(mm)	1/4 / (6,35)
Maximum Torque Nm/(ft-lb)	30/(22)
Working Torque Range Nm/(ft-lb)	0-25/(0-18)
Bolt Cap mm/(in.)	6,35/(1/4)
Free Speed r.p.m.	300
Weight kg/(lb)	0,39/(0,86)
Noise Level dBA/(power)	77/(88)
Vibration a/k m/s ²	6,1/1,1
Max Air Consumption CFM/(L/S)	10,8/(5,1)
Avg Air Consumption CFM/(L/S)	1,8/(0,8)
Air Inlet Size in.	1/8

SI-1108B

3/8" Ratchet Wrench

- Super small ratchet wrench with 3/8"sq. anvil
- Smaller than SI-1200B & SI-1205B




Shank Size in./(mm)	3/8 / (9,5)
Maximum Torque Nm/(ft-lb)	30/(22)
Working Torque Range Nm/(ft-lb)	0-25/(0-18)
Bolt Cap mm/(in.)	10/(3/8)
Free Speed r.p.m.	300
Weight kg/(lb)	0,40/(0,88)
Noise Level dBA/(power)	77/(88)
Vibration a/k m/s ²	6,4/1,1
Max Air Consumption CFM/(L/S)	10,8/(5,1)
Avg Air Consumption CFM/(L/S)	1,8/(0,8)
Air Inlet Size in.	1/8

SI-1217EX

1/4" Ratchet Wrench

- The durable ratchet mechanism increased the lifetime by 30% than before
- Double mold composite body cover for added vibration and cold temperature protection.
- 360° air inlet swivel.




Shank Size in./(mm)	1/4 / (6,35)
Maximum Torque Nm/(ft-lb)	43/(31)
Working Torque Range Nm/(ft-lb)	0-36/(0-26)
Bolt Cap mm/(in.)	6,35/(1/4)
Free Speed r.p.m.	300
Weight kg/(lb)	0,54/(1,19)
Noise Level dBA/(power)	84/(95)
Vibration a/k m/s ²	4,0/0,9
Max Air Consumption CFM/(L/S)	9,6/(4,5)
Avg Air Consumption CFM/(L/S)	1,6/(0,8)
Air Inlet Size in.	1/4

SI-1218EX

3/8" Ratchet Wrench

- The durable ratchet mechanism increased the lifetime by 30% than before
- Double mold composite body cover for added vibration and cold temperature protection.
- 360° air inlet swivel.




Shank Size in./(mm)	3/8 / (9,5)
Maximum Torque Nm/(ft-lb)	45/(35)
Working Torque Range Nm/(ft-lb)	0-36/(0-26)
Bolt Cap mm/(in.)	10/(3/8)
Free Speed r.p.m.	300
Weight kg/(lb)	0,54/(1,20)
Noise Level dBA/(power)	88/(99)
Vibration a/k m/s ²	4,5/0,9
Max Air Consumption CFM/(L/S)	9,6/(4,5)
Avg Air Consumption CFM/(L/S)	1,6/(0,8)
Air Inlet Size in.	1/4

SI-1200B

1/4" Ratchet Wrench

- Light and small ratchet wrench with 1/4"sq. anvil
- This model is the "Mini Ratchet Wrench" standard in the air tools industry




Shank Size in./(mm)	1/4 / (6,35)
Maximum Torque Nm/(ft-lb)	35/(25)
Working Torque Range Nm/(ft-lb)	0-30/(0-22)
Bolt Cap mm/(in.)	6,35/(1/4)
Free Speed r.p.m.	200
Weight kg/(lb)	0,51/(1,11)
Noise Level dBA/(power)	82/(93)
Vibration a/k m/s ²	3,6/0,8
Max Air Consumption CFM/(L/S)	9,6/(4,5)
Avg Air Consumption CFM/(L/S)	1,6/(0,8)
Air Inlet Size in.	1/4

SI-1205B

3/8" Ratchet Wrench

- Light and small ratchet wrench with 3/8"sq. anvil
- This model is the "Mini Ratchet Wrench" standard in the air tools industry




Shank Size in./(mm)	3/8 / (9,5)
Maximum Torque Nm/(ft-lb)	40/(30)
Working Torque Range Nm/(ft-lb)	0-30/(0-22)
Bolt Cap mm/(in.)	10/(3/8)
Free Speed r.p.m.	220
Weight kg/(lb)	0,51/(1,12)
Noise Level dBA/(power)	82/(93)
Vibration a/k m/s ²	5,7/1,0
Max Air Consumption CFM/(L/S)	9,6/(4,5)
Avg Air Consumption CFM/(L/S)	1,6/(0,8)
Air Inlet Size in.	1/4

SI-1251

1/4" Ratchet Wrench

- Japan and foreign patent(s) pending as the "Slide Switch" for the reverse function
- Plastic covered small size body
- 1/4"sq. anvil





Shank Size in./(mm)	1/4 / (6,35)
Maximum Torque Nm/(ft-lb)	45/(33)
Working Torque Range Nm/(ft-lb)	0-33/(0-24)
Bolt Cap mm/(in.)	6,35/(1/4)
Free Speed r.p.m.	200
Weight kg/(lb)	0,56/(1,24)
Noise Level dBA/(power)	75/(86)
Vibration a/k m/s ²	4,0/0,8
Max Air Consumption CFM/(L/S)	14,4/(6,6)
Avg Air Consumption CFM/(L/S)	2,4/(1,1)
Air Inlet Size in.	1/4

SI-1252

3/8" Ratchet Wrench

- Japan and foreign patent(s) pending as the "Slide Switch" for the reverse function
- Plastic covered small size body
- 3/8"sq. anvil




Shank Size in./(mm)	3/8 / (9,5)
Maximum Torque Nm/(ft-lb)	47/(35)
Working Torque Range Nm/(ft-lb)	0-35/(0-26)
Bolt Cap mm/(in.)	10/(3/8)
Free Speed r.p.m.	200
Weight kg/(lb)	0,56/(1,24)
Noise Level dBA/(power)	75/(86)
Vibration a/k m/s ²	3,9/0,8
Max Air Consumption CFM/(L/S)	14,4/(6,6)
Avg Air Consumption CFM/(L/S)	2,4/(1,1)
Air Inlet Size in.	1/4

SI-1340 EX

3/8" Ratchet Wrench

- Premium quality ratchet wrench with a rear exhaust and composite body cover.
- Low noise levels and precise planetary gear mechanism for maximum power transfer and durability.
- 360° air inlet swivel.




Shank Size in./(mm)	3/8 / (9,5)
Maximum Torque Nm/(ft-lb)	110/(81)
Working Torque Range Nm/(ft-lb)	0-85/(0-63)
Bolt Cap mm/(in.)	12/(1/2)
Free Speed r.p.m.	160
Weight kg/(lb)	1,14/(2,50)
Noise Level dBA/(power)	82/(93)
Vibration a/k m/s ²	4,2/0,9
Max Air Consumption CFM/(L/S)	15,0/(7,1)
Avg Air Consumption CFM/(L/S)	2,5/(1,2)
Air Inlet Size in.	1/4

SI-1345 EX

1/2" Ratchet Wrench

- Premium quality ratchet wrench with a rear exhaust and composite body cover.
- Low noise levels and precise planetary gear mechanism for maximum power transfer and durability.
- 360° air inlet swivel.




Shank Size in./(mm)	1/2 / (12,7)
Maximum Torque Nm/(ft-lb)	115/(85)
Working Torque Range Nm/(ft-lb)	0-90/(0-66)
Bolt Cap mm/(in.)	14/(9/16)
Free Speed r.p.m.	160
Weight kg/(lb)	1,15/(2,53)
Noise Level dBA/(power)	82/(93)
Vibration a/k m/s ²	4,1/0,9
Max Air Consumption CFM/(L/S)	15,0/(7,1)
Avg Air Consumption CFM/(L/S)	2,5/(1,2)
Air Inlet Size in.	1/4

SI-1320A

3/8" Ratchet Wrench

- Standard ratchet wrench with the front exhaust 3/8"sq. anvil
- Reasonable price




Shank Size in./(mm)	3/8 / (9,5)
Maximum Torque Nm/(ft-lb)	80/(59)
Working Torque Range Nm/(ft-lb)	0-60/(0-44)
Bolt Cap mm/(in.)	12/(1/2)
Free Speed r.p.m.	160
Weight kg/(lb)	1,16/(2,57)
Noise Level dBA/(power)	89/(100)
Vibration a/k m/s ²	6,3/1,1
Max Air Consumption CFM/(L/S)	16,2/(7,6)
Avg Air Consumption CFM/(L/S)	2,7/(1,3)
Air Inlet Size in.	1/4

SI-1325A

1/2" Ratchet Wrench

- Standard ratchet wrench with the front exhaust 1/2"sq. anvil
- Best selling model in the world at a reasonable price



Shank Size in./(mm)	1/2 / (12,7)
Maximum Torque Nm/(ft-lb)	90/(66)
Working Torque Range Nm/(ft-lb)	0-70/(0-52)
Bolt Cap mm/(in.)	14/(9/16)
Free Speed r.p.m.	160
Weight kg/(lb)	1,17/(2,58)
Noise Level dBA/(power)	89/(100)
Vibration a/k m/s ²	6,3/1,1
Max Air Consumption CFM/(L/S)	15,0/(7,1)
Avg Air Consumption CFM/(L/S)	2,5/(1,3)
Air Inlet Size in.	1/4