

IMPACT WRENCHES

- 1/4" IMPACT WRENCHES
- 3/8" IMPACT WRENCHES
- 1/2" IMPACT WRENCHES
- 3/4" IMPACT WRENCHES
- 1" IMPACT WRENCHES
- 1-1/2" IMPACT WRENCH

SI-1490BSR

SI-1310S

1/4" Impact Wrench

Double Hammer



- Composite body absorbs the vibration remarkably well and also protects your hand from the cold.
- Compact, lightweight, and a "feather touch" trigger for easy operation.
- Rear exhaust from handle-end directs air away from operator and workplace.



SI-1310S
Maximum Torque :
40Nm

SI-1315S

3/8" Impact Wrench



SI-1315S
Maximum Torque :
60Nm

	SI-1310S	SI-1315S
Maximum Torque Nm/(ft-lb)	40/(30)	60/(44)
Working Torque Range Nm/(ft-lb)	0-35/(0-26)	0-50/(0-37)
Bolt Cap mm/(in.)	8/(5/16)	10/(3/8)
Free Speed r.p.m.	10,000	10,000
Weight kg/(lb)	0.63/(1.39)	0.63/(1.29)
Noise Level dBA/(power)	86/(97)	86/(97)
Vibration a/k m/s ²	4.8/(0.9)	4.9/(1.0)
Max Air Consumption CFM/(L/S)	12.6/(5.9)	12.6/(5.9)
Avg Air Consumption CFM/(L/S)	2.1/(1.0)	2.1/(1.0)
Air Inlet Size in.	1/4	1/4
Hose Size mm/(in.)	10/(3/8)	10/(3/8)

SI-1355

3/8" Impact Wrench

Single Hammer




Maximum Torque :
90Nm

Maximum Torque Nm/(ft-lb)	90/(66)
Working Torque Range Nm/(ft-lb)	0-75/(0-55)
Bolt Cap mm/(in.)	10/(3/8)
Free Speed r.p.m.	9,000
Weight kg/(lb)	1.12/(2.47)
Noise Level dBA/(power)	86/(91)
Vibration a/k m/s ²	3.3/(0.8)
Max Air Consumption CFM/(L/S)	16.2/(7.6)
Avg Air Consumption CFM/(L/S)	2.7/(1.5)
Air Inlet Size in.	1/4
Hose Size mm/(in.)	10/(3/8)

SI-1365

3/8" Impact Wrench

Double Hammer




Maximum Torque :
100Nm

Maximum Torque Nm/(ft-lb)	100/(74)
Working Torque Range Nm/(ft-lb)	0-80/(0-59)
Bolt Cap mm/(in.)	10/(3/8)
Free Speed r.p.m.	8,000
Weight kg/(lb)	1.31/(2.89)
Noise Level dBA/(power)	91/(102)
Vibration a/k m/s ²	8.3/(1.2)
Max Air Consumption CFM/(L/S)	19.8/(9.3)
Avg Air Consumption CFM/(L/S)	3.3/(1.6)
Air Inlet Size in.	1/4
Hose Size mm/(in.)	10/(3/8)

SI-1305

3/8" Impact Wrench

Single Hammer



Maximum Torque :
90Nm

Maximum Torque Nm/(ft-lb)	90/(66)
Working Torque Range Nm/(ft-lb)	0-75/(0-55)
Bolt Cap mm/(in.)	10/(3/8)
Free Speed r.p.m.	9,000
Weight kg/(lb)	0.94/(2.08)
Noise Level dBA/(power)	91/(102)
Vibration a/k m/s ²	3.8/(0.8)
Max Air Consumption CFM/(L/S)	16.8/(7.9)
Avg Air Consumption CFM/(L/S)	2.8/(1.3)
Air Inlet Size in.	1/4
Hose Size mm/(in.)	10/(3/8)

SI-1650AH

1/2" Impact Wrench

Twin Hammer



Maximum Torque :
350Nm

Maximum Torque Nm/(ft-lb)	350/(258)
Working Torque Range Nm/(ft-lb)	0-280/(0-207)
Bolt Cap mm/(in.)	16/(5/8)
Free Speed r.p.m.	(F)7,500 (R)8,000
Weight kg/(lb)	2.80/(6.17)
Noise Level dBA/(power)	91/(102)
Vibration a/k m/s ²	18.1/(2.2)
Max Air Consumption CFM/(L/S)	24.0/(11.3)
Avg Air Consumption CFM/(L/S)	4.0/(1.9)
Air Inlet Size in.	1/4
Hose Size mm/(in.)	10/(3/8)

SI-1420T

1/2" Impact Wrench

Twin Hammer



Maximum Torque :
500Nm

Maximum Torque Nm/(ft-lb)	500/(369)
Working Torque Range Nm/(ft-lb)	0-400/(0-295)
Bolt Cap mm/(in.)	18/(1.1/16)
Free Speed r.p.m.	6,000
Weight kg/(lb)	2.55/(5.62)
Noise Level dBA/(power)	91/(102)
Vibration a/k m/s ²	7.3/(1.2)
Max Air Consumption CFM/(L/S)	24.4/(11.3)
Avg Air Consumption CFM/(L/S)	4.8/(1.9)
Air Inlet Size in.	1/4
Hose Size mm/(in.)	10/(3/8)

SI-1422T

1/2" Impact Wrench with 2" Extended Anvil

Twin Hammer



Maximum Torque :
480Nm

Maximum Torque Nm/(ft-lb)	480/(354)
Working Torque Range Nm/(ft-lb)	0-360/(0-265)
Bolt Cap mm/(in.)	18/(1.1/16)
Free Speed r.p.m.	6,000
Weight kg/(lb)	2.65/(5.82)
Noise Level dBA/(power)	92/(103)
Vibration a/k m/s ²	8.2/(1.3)
Max Air Consumption CFM/(L/S)	24.0/(11.3)
Avg Air Consumption CFM/(L/S)	4.0/(1.9)
Air Inlet Size in.	1/4
Hose Size mm/(in.)	10/(3/8)