

SI-2740

10mm Belt Sander

- 10mm sanding belt sander
- Super light & ergonomic design
- Rubber grip giving comfortable vibration

OPTION

509-45Z/40 10mm Sanding belt #40
509-45Z/80 10mm Sanding belt #80
509-45Z/100 10mm Sanding belt #100
509-45Z/120 10mm Sanding belt #120

SI-2741

12mm Belt Sander

Adjustable 160° Sanding arm

Light weight composite construction

Includes air regulator for quick speed adjustment

Quick change belt replacement lever

	SI-2740	SI-2741
Belt Size mm	10 x 330	12 x 330
Free Speed rpm	15,000	15,000
Out Put Watt	317	317
Weight kg/(lb)	0.73/(1.61)	0.73/(1.61)
Noise Level dBA/(power)	85/(96)	85/(96)
Vibration a/k m/s ²	1.0/0.6	1.0/0.6
Max Air Consumption CFM/(L/S)	19.8/(9.3)	19.8/(9.3)
Avg Air Consumption CFM/(L/S)	3.3/(1.6)	3.3/(1.6)

Standard Accessory

509-60Z/12 12mm Sanding belt #60x6

SI-2700

10mm Belt Sander

- 10mm sanding belt sander
- Quick and easy belt change
- Adjustable arm angle

OPTION

509-45Z/40 10mm Sanding belt #40
509-45Z/80 10mm Sanding belt #80
509-45Z/100 10mm Sanding belt #100
509-45Z/120 10mm Sanding belt #120

Adjustable 160° Sanding arm

Quick change belt replacement lever

	SI-2700
Belt Size mm	10x330
Free Speed rpm	15,000
Out Put Watt	317
Weight kg/(lb)	0.82/(1.82)
Noise Level dBA/(power)	85/(99)
Vibration a/k m/s ²	2.2/0.7
Max Air Consumption CFM/(L/S)	19.8/(9.3)
Avg Air Consumption CFM/(L/S)	3.3/(1.6)

Standard Accessory

509-60Z/60 10mm Sanding belt #60x6

SI-2700L

10mm Belt Sander

Head rotates 120 degrees for operating convenience. Variable speed throttle for positive control.

- Best for the light grinding, sanding and deburring. (SI-2700L)
- For nugget grinding of spot welding. (SI-2700LS)

SI-2700LS

13mm Belt Sander

	SI-2700L	SI-2700LS
Belt Size mm	10x460	13x460
Free Speed rpm	15,000	15,000
Out Put Watt	317	317
Weight kg/(lb)	0.85/(1.87)	0.9/(1.98)
Noise Level dBA/(power)	83/(94)	84/(95)
Vibration a/k m/s ²	2.5/0.7	1.8/0.6
Max Air Consumption CFM/(L/S)	19.8/(9.3)	19.8/(9.3)
Avg Air Consumption CFM/(L/S)	3.3/(1.6)	3.3/(1.6)

Standard Accessory

509-130 10mm Felt belt #60 x 1
509-131 10mm Felt belt #150 x 1
509-132 10mm Felt belt #320 x 1

Standard Accessory

509LK-106 13mm Sanding belt #60 x 5

SI-2800

20mm Belt Sander

- 20mm sanding belt sander
- Safety cover over belt wheel

OPTION

507-58Z/40 20mm Sanding belt #40
507-58Z/80 20mm Sanding belt #80
507-58Z/100 20mm Sanding belt #100
507-58Z/120 20mm Sanding belt #120

SI-2830

30mm Belt Sander

- 30mm sanding belt sander
- Safety cover over belt wheel
- Side handle for firm tool control

OPTION

505-56Z/40 30mm Sanding belt #40
505-56Z/80 30mm Sanding belt #80
505-56Z/100 30mm Sanding belt #100
505-56Z/120 30mm Sanding belt #120

	SI-2800	SI-2830
Belt Size mm	20x520	30x540
Free Speed rpm	15,000	10,000
Out Put Watt	429	582
Weight kg/(lb)	1.43/(3.14)	2.02/(4.45)
Noise Level dBA/(power)	84/(95)	86/(97)
Vibration a/k m/s ²	3.0/0.8	1.8/0.6
Max Air Consumption CFM/(L/S)	22.8/(10.8)	31.8/(15.0)
Avg Air Consumption CFM/(L/S)	3.8/(1.8)	5.3/(2.5)

Standard Accessory

507-58Z/60 20mm Sanding belt #60x6

Standard Accessory

505-56Z/60 30mm Sanding belt #60x6

SI-3121-6

Central Vacuum Dual Action Sander with 6" pad

- Central vacuum dual action sander for dust extraction system and vacuum cleaner
- Light weight and compact palm grip body
- 6" Multihole pad giving speedy operation

SI-3121

SI-3121M - Velcro pad model

Central Vacuum Dual Action Sander with 5" pad

	SI-3121-6	SI-3121/3121M
Pad/Disc Size mm/(in.)	150(6")	125(5")
Spindle Size	5/16-24UNF	5/16-24UNF
Orbit Dia mm	5	5
Free Speed rpm	10,000	10,000
Out Put Watt	148	148
Weight kg/(lb)	1.31/(2.88)	1.29/(2.83)
Noise Level dBA/(power)	81/(92)	81/(92)
Vibration a/k m/s ²	13.4/1.8	12.8/1.7
Max Air Consumption CFM/(L/S)	13.8/(6.5)	13.8/(6.5)
Avg Air Consumption CFM/(L/S)	2.3/(1.1)	2.3/(1.1)

Standard Accessory

M-150HDMH 6" Velcro
1041 CV-5 6" Face Cover
#240x1 #120x1 6" Net paper
NP-150-240 NP-150-120 6" Net paper

Standard Accessory

M-125H 5" Velcro
P-125HC 5" Leather
570-42A 5" Velcro

SI-3101G

Dual Action Sander with 5" leather pad

- Low center of gravity dual action sander.
- The stable power can fully be delivered.
- Super light weight and easy to grip composite body cover.

SI-3101LGM

Dual Action Sander with 5" velcro pad

	SI-3101G	SI-3101LGM
Pad/Disc Size mm/(in.)	125(5")	125(5")
Spindle Size	5/16-24UNF	5/16-24UNF
Orbit Dia mm	5	5
Free Speed rpm	10,000	10,000
Out Put Watt	148	148
Weight kg/(lb)	0.88/(1.94)	0.88/(1.94)
Noise Level dBA/(power)	89/(99)	89/(99)
Vibration a/k m/s ²	13.7/1.8	13.2/(6.2)
Max Air Consumption CFM/(L/S)	13.2/(6.2)	13.2/(6.2)
Avg Air Consumption CFM/(L/S)	2.2/(1.0)	2.2/(1.0)

Standard Accessory

P-125H 5" Leather
M-125H 5" Velcro

SI-3111G

Self vacuum Dual Action Sander with 5" leather pad

- Low center of gravity self vacuum dual action sander.
- The stable power can fully be delivered.
- Super light weight and easy to grip composite body cover.

SI-3111LGM

Self vacuum Dual Action Sander with 5" velcro pad

	SI-3111G	SI-3111LGM
Pad/Disc Size mm/(in.)	125(5")	125(5")
Spindle Size	5/16-24UNF	5/16-24UNF
Orbit Dia mm	5	5
Free Speed rpm	10,000	10,000
Out Put Watt	148	148
Weight kg/(lb)	1.23/(2.71)	1.23/(2.71)
Noise Level dBA/(power)	89/(99)	89/(99)
Vibration a/k m/s ²	13.7/1.8	13.7/1.8
Max Air Consumption CFM/(L/S)	13.8/(6.5)	13.8/(6.5)
Avg Air Consumption CFM/(L/S)	2.3/(1.1)	2.3/(1.1)

Standard Accessory

P-125HD 5" Leather
M-125HD 5" Velcro

Standard Accessory

1040-54 485-42

SI-3103B

SI-3103BM - Velcro pad model

Dual Action Sander with 5" pad

- Heavy duty action sander for factory work.
- Powerful high quality air motor.
- Durable mechanism ensures a long working life.

SI-3103M

SI-3103M - Velcro pad model

Heavy Duty Type

	SI-3103B	SI-3103M
Pad/Disc Size mm/(in.)	125(5")	125(5")
Spindle Size	5/16-24UNF	5/16-24UNF
Orbit Dia mm	5	5
Free Speed rpm	9,000	9,000
Out Put Watt	134	134
Weight kg/(lb)	1.18/(2.60)	1.18/(2.60)
Noise Level dBA/(power)	87/(96)	87/(96)
Vibration a/k m/s ²	15.6/2.0	15.6/2.0
Max Air Consumption CFM/(L/S)	16.8/(7.9)	16.8/(7.9)
Avg Air Consumption CFM/(L/S)	2.8/(1.3)	2.8/(1.3)

Standard Accessory

P-125H 5" Leather
M-125H 5" Velcro