


8561 B - 8566 BL
Torque wrench DREMOMETER
25-120 Nm / 18-90 lbf-ft




- > Torque wrench with 1/2" square drive in the range of 25 - 120 Nm
- > Single- and double-square drive for controlled bi-directional tightening
- > You can feel and hear an audible automatic click
- > Double scale for measuring ranges in lbf-ft range



- > Highest accuracy max. deviation of +/- 3 %
- > Error-free operation - no change in torque values when operated outside the handle
- > Certificate according to DIN EN ISO 6789:2017 part 2
- > Power-saving through the use of optional extension tubes

Code	No.	Type	"	mm	Storage	Contents	Nm	lbf-ft	lw	a	b	c	Scale	Weight
2926989	8561-001	Single square rigid	1/2"	12,5	Plastic box	ALU-extension tube No. 8577-350	25-120	18-90	373	30	17,5	462	5 Nm / 5 lbf-ft	2,2
7683320	8561-01	Single square rigid	1/2"	12,5	Plastic box		25-120	18-90	373	30	17,5	462	5 Nm / 5 lbf-ft	1,5
7683400	8566-01	Double square rigid	1/2"	12,5	Plastic box		25-120	18-90	373	30	17,5	462	5 Nm / 5 lbf-ft	1,5

8573 BC - 8578 BCL
Torque wrench DREMOMETER
40-200 Nm / 30-150 lbf-ft




- > Torque wrenches with 1/2" square drive in the range of 40 - 200 Nm
- > Single- and double-square drive for controlled bi-directional tightening
- > You can feel and hear an audible automatic click
- > Double scale for measuring ranges in lbf-ft range



- > Highest accuracy max. deviation of +/- 3 %
- > Error-free operation - no change in torque values when operated outside the handle
- > Certificate according to DIN EN ISO 6789:2017 part 2
- > With push-button release

Code	No.	Type	"	mm	Storage	Nm	lbf-ft	lw	a	b	c	Scale	Weight
7685530	8573-00	Single square rigid	1/2"	12,5	Plastic box	40-200	30-150	463	30	17,5	551	5 Nm / 5 lbf-ft	1,4
7683590	8573-02	Single square rigid	1/2"	12,5	Plastic box	40-200	30-150	463	30	17,5	551	5 Nm / 5 lbf-ft	3,5
7683670	8578-00	Double square rigid	1/2"	12,5	Plastic box	40-200	30-150	463	30	17,5	551	5 Nm / 5 lbf-ft	1,4

8562 C - 8567 CL
Torque wrench DREMOMETER
60-300 Nm / 45-220 lbf-ft



- > Torque wrenches with 1/2" square drive in the range of 60 - 300 Nm
- > Single- and double-square drive for controlled bi-directional tightening
- > You can feel and hear an audible automatic click
- > Double scale for measuring ranges in lbf-ft range



- > Highest accuracy max. deviation of +/- 3 %
- > Error-free operation - no change in torque values when operated outside the handle
- > Certificate according to DIN EN ISO 6789:2017 part 2
- > Power-saving through the use of optional extension tubes

Code	No.	Type	"	mm	Storage	Contents	Nm	lbf-ft	lw	a	b	c	Scale	Weight
2926997	8562-001	Single square rigid	1/2"	12,5	Plastic box	ALU-extension tube No. 8577-700	60-300	45-220	529	30	17,5	617	5 Nm / 5 lbf-ft	2,7
7685450	8562-10	Single square rigid	1/2"	12,5	Plastic box		60-300	45-220	529	30	17,5	617	5 Nm / 5 lbf-ft	2,0
7685960	8567-10	Double square rigid	1/2"	12,5	Plastic box		60-300	45-220	529	30	17,5	617	5 Nm / 5 lbf-ft	2,3