


SI-2005HD

Die Grinder

- Small body size, angle head die grinder with a polymer grip cover
- High durability die grinder
- Compact, lightweight, ergonomic design and feather touch throttle lever for easy operation.
- A plastic body cover absorbs tool vibrations and protects your hand from the cold
- Lever throttle with safety lock



SI-2005HD-6

Die Grinder

6mm Collet model

SI-2005HD SI-2005HD-6

Collet Size	ø1/4"	ø6mm
Free Speed rpm (MAX)	20,000	20,000
Output Watt	200	200
Weight kg/(lb)	0.56/(1.23)	0.56/(1.23)
Noise Level dBA/(power)	81/(92)	81/(92)
Vibration a/k m/s ²	7.3/1.2	7.3/1.2
Max Air Consumption CFM/(L/S)	14.4/(6.8)	14.4/(6.8)
Avg Air Consumption CFM/(L/S)	2.4/(1.1)	2.4/(1.1)


SI-2006S

Die Grinder

SI-2006S-6

6mm Collet model

- Small body size, angle head die grinder
- 1/4" collet and 6mm collets are available
- Compact, lightweight, ergonomic design and feather touch throttle lever for easy operation
- Lever throttle with safety lock




SI-2006S
SI-2006S-6

Collet Size	ø1/4"
Free Speed rpm (MAX)	20,000
Output Watt	127
Weight kg/(lb)	0.49/(1.08)
Noise Level dBA/(power)	83/(94)
Vibration a/k m/s ²	7.4/1.6
Max Air Consumption CFM/(L/S)	13.8/(6.5)
Avg Air Consumption CFM/(L/S)	2.3/(1.1)

SI-2033

Cut off Grinder

- A straight grinder designed for 3" cut off discs
- For cutting sheet metal or pipe
- Especially useful for cutting the exhaust pipe on motorcars
- Compact and lightweight body with lever throttle for safety operation



Disc Size mm/(in.)	75/(3")
Spindle Size	ø9.5/(3/8")
Free Speed rpm (MAX)	20,000
Output Watt	347
Weight kg/(lb)	1.00/(2.21)
Noise Level dBA/(power)	89/(100)
Vibration a/k m/s ²	7.5/2.4
Max Air Consumption CFM/(L/S)	24.0/(11.3)
Avg Air Consumption CFM/(L/S)	4.0/(1.9)


SI-2022S

Die Grinder

SI-2022S-6

6mm Collet model

- Die grinder with the extended shaft
- 1/4" collet and 6mm collets are available
- Special designed extended die grinder for unreachable place



SI-2022S
SI-2022S-6

Collet Size	ø1/4"
Free Speed rpm (MAX)	24,000
Output Watt	537
Weight kg/(lb)	1.34/(2.94)
Noise Level dBA/(power)	89/(100)
Vibration a/k m/s ²	4.1/0.9
Max Air Consumption CFM/(L/S)	27.0/(12.7)
Avg Air Consumption CFM/(L/S)	4.5/(2.1)


SI-2023

Die Grinder

SI-2023-6

6mm Collet model

- Low Speed Die Grinder
- 1/4" collet and 6mm collets are available
- Sander with the extended shaft
- Special designed extended Sander for unreachable place



SI-2023
SI-2023-6

Collet Size	ø1/4"
Free Speed rpm (MAX)	6,000
Output Watt	436
Weight kg/(lb)	1.70/(3.75)
Noise Level dBA/(power)	90/(101)
Vibration a/k m/s ²	4.0/0.9
Max Air Consumption CFM/(L/S)	22.8/(10.8)
Avg Air Consumption CFM/(L/S)	3.8/(1.9)

SI-2501L

Disc Grinder
Lever Switch

- Light weight 4" disc grinder with rotary throttle
- 40% lighter than SI-2500
- Speed governor assures safety operation
- Precise gear mechanism assures the highest power transfer, durability and reduced vibration



SI-2501

Disc Grinder
Rotary Switch

Standard Accessory	
4" Disc 15mm Hole 240-6 SI-2501	4" Disc 16mm Hole 240-71 SI-2501L
Standard Accessory	
Disc Nut for 15mm Hole 380-44 SI-2501	Disc Nut for 16mm Hole 240C-1 SI-2501L

SI-2501L		SI-2501	
Disc Size mm/(in.)	100/(4")	100/(4")	
Spindle Size	M10x1.5	M10x1.5	
Free Speed rpm (MAX)	13,000	13,000	
Output Watt	303	303	
Weight kg/(lb)	1.04/(2.29)	0.81/(2.01)	
Noise Level dBA/(power)	81/(92)	82/(93)	
Vibration a/k m/s ²	9.6/3.1	8.4/2.8	
Max Air Consumption CFM/(L/S)	16.2/(7.5)	13.2/(6.2)	
Avg Air Consumption CFM/(L/S)	2.7/(1.3)	2.2/(1.0)	

SI-2500L

Disc Grinder
Lever Switch

- The high quality air motor used ensures the highest power and durability, while reducing vibration
- A trouble free tool for industry use




Standard Accessory	
4" Disc 16mm Hole 240-71	Disc Nut for 16mm Hole 240C-1

SI-2500L		SI-2500	
Disc Size mm/(in.)	100/(4")	100/(4")	
Spindle Size	M10x1.5	M10x1.5	
Free Speed rpm (MAX)	12,700	12,700	
Output Watt	443	443	
Weight kg/(lb)	1.82/(4.02)	1.87/(4.11)	
Noise Level dBA/(power)	80/(91)	84/(95)	
Vibration a/k m/s ²	9.3/3.2	7.6/2.5	
Max Air Consumption CFM/(L/S)	16.2/(7.5)	14.4/(6.8)	
Avg Air Consumption CFM/(L/S)	2.7/(1.3)	2.4/(1.1)	

SI-2515LA

Disc Grinder

- 5" Disc grinder with safety lever throttle and 14mm thread spindle
- Speed governor assures safety operation
- Spindle lock button enable exchanging disc quickly
- Rear exhaust and lever throttle with safety lock
- Disc one push lock button model




Disc Size mm/(in.)	125/(5")
Spindle Size	M14x2
Free Speed rpm (MAX)	12,000
Output Watt	570
Weight kg/(lb)	1.93/(4.27)
Noise Level dBA/(power)	85/(96)
Vibration a/k m/s ²	11.0/3.6
Max Air Consumption CFM/(L/S)	16.8/(7.9)
Avg Air Consumption CFM/(L/S)	2.8/(1.3)

SI-2505L

Disc Grinder

- 5" Disc grinder with safety lever throttle
- For this model because of the safety reason
- Speed governor assures safety operation
- Lever throttle with safety lock



Disc Size mm/(in.)	125/(5")
Disc Hole Size	ø22/(7/8")
Free Speed rpm (MAX)	12,000
Output Watt	443
Weight kg/(lb)	1.91/(4.22)
Noise Level dBA/(power)	82/(93)
Vibration a/k m/s ²	5.8/1.9
Max Air Consumption CFM/(L/S)	19.8/(9.3)
Avg Air Consumption CFM/(L/S)	3.3/(1.6)