

Torque Tools

Quickset

Torque screwdriver Typ Quickset
0,24-9 Nm



- > Adjustable torque screwdriver with scale
- > 1/4" hexagon socket for 1/4" bits - C 6.3
- > With slip clutch for error proof controlled right and left hand tightening

- > It is not possible to over-tighten the screw
- > Certificate according to DIN EN ISO 6789 maximum deviation +/- 6%
- > Models No. QSN600 FH + QSN900 FH with additional cross handle



| Code | No. | Hex " | Hex mm | cNm | Nm | mm | kg |
|---------|---------------|-------|--------|---------|----------|-----|-------|
| 7718050 | QSM/N FH BLUE | 1/4" | 6.3 | 24-120 | 0,24-1,2 | 169 | 0,165 |
| 7718130 | QS6 FH BLUE | 1/4" | 6.3 | 120-600 | 1,2-6 | 184 | 0,335 |
| 7718210 | QS9 FH BLUE | 1/4" | 6.3 | 400-900 | 4-9 | 184 | 0,335 |

TT

Torque screwdriver Type SP
10-500 cNm / 14 ozf-in-40 lbf-in



- > Indicating torque test screwdriver with double scale
- > With slave-pointer function works in both directions
- > For controlled bi-directional tightening
- > 1/4" hexagon socket for 1/4" bits - C 6.3

- > Certificate according to DIN EN ISO 6789 maximum deviation +/- 6%
- > EPA (Electrostatic Protected Area) compliant
- > Models No. TT250 FH BLUE + TT500 FH BLUE with additional cross handle



| Code | No. | Hex " | Hex mm | cNm | Nm | ozf-in / lbf-in | mm | kg |
|---------|---------------|-------|--------|---------|---------|-----------------|-----|-------|
| 7096380 | TT50 FH BLUE | 1/4" | 6.3 | 10-50 | 0,1-0,5 | 14-70 | 178 | 0,190 |
| 7096460 | TT100 FH BLUE | 1/4" | 6.3 | 20-100 | 0,2-1 | 28-140 | 178 | 0,190 |
| 7096540 | TT250 FH BLUE | 1/4" | 6.3 | 50-250 | 0,5-2,5 | 4-20 | 250 | 0,465 |
| 7096620 | TT500 FH BLUE | 1/4" | 6.3 | 100-500 | 1-5 | 8-40 | 250 | 0,465 |

TSN

Torque wrench TSN SLIPPER
1-125 Nm / 10-1106 lbf-in / fixed setting



- > Fixed torque wrench for series assembly
- > 1/4", 3/8" or 1/2" square drive with integrated ratchet function
- > For error proof controlled directional tightening
- > It is not possible to over-tighten the screw
- > Certificate according to DIN EN ISO 6789 +/- 4% tolerance

- > Fixed setting at GEDORE or by hand on a test device
- > If ordering, please specify the Nm value - if a fixed factory pre-setting is desired (price on request)
- > EPA (Electrostatic Protected Area) compliant

| Code | No. | Hex " | Hex mm | Nm | lbf-in | mm | kg |
|---------|----------|-------|--------|--------|----------|-----|------|
| 7091900 | TSN 25 D | 1/4" | 6,3 | 5-25 | 44-221 | 216 | 0,34 |
| 7092040 | TSN 25 A | 3/8" | 10 | 5-25 | 44-221 | 216 | 0,34 |
| 7092120 | TSN 55 | 3/8" | 10 | 55 | 132-486 | 324 | 0,80 |
| 7092200 | TSN 125 | 1/2" | 12,5 | 40-125 | 354-1106 | 460 | 1,36 |