Adjustable Wrenches



ADJUSTABLE WRENCHES

- · High-grade alloy steel.
- · Nickel based plating with brushed finish to reduce rust and corrosion.
- Forged and heat-treated for durability.
- · Jaw scales in SAE and metric for quick adjustment.

Catalog No.	Model No.	Description	Nom. Size		Jaw Opening		Weight		Std.
oatalog No.			in	mm	in	mm	lb	kg	Pack
86902	756	6" Adjustable Wrench	6	150	3/4	20	1/4	0.1	F
86907	758	8" Adjustable Wrench	8	200	7/8	22	1/2	0.2	5
86912	760	10" Adjustable Wrench	10	250	1 1/8	30	3/4	0.3	4
86917	762	12" Adjustable	12	300	1 5/16	35	1 1/2	0.6	
86922	765	15" Adjustable	15	375	1 11/16	40	3	1.3	
86927	768	18" Adjustable	18	450	2 1/8	50	5 ½	2.3	-
86932	774	24" Adjustable	24	600	2 7/16	60	9 1/4	4.2	1

Specific Purpose Wrenches



TELESCOPING BASIN WRENCH

- Innovative design makes working with faucet fittings and retaining nuts easier than ever.
- · Built-in, water-resistant LED light provides direct illumination of your work.
- Pivoting, removable T-handle allows you easier access in tight spaces.
- 3/" square drive connection lets you use your ratchet or breaker bar for additional leverage and maximum torque.
- Ergonomic textured handle increases leverage and improves grip.
- New body design enables effortless telescoping from 10" to 17"

	Catalog No.	Model No.	Description	Nom. Size		e Pipe Capacity		Weight		Std.
			Description	in	mm	in	mm	lb	kg	Pack
	46753	2017	Telescoping Basin Wrench	10 - 17	240 - 425	1/2 - 1 1/4	12 - 32	2 ½	1.2	1



BASIN WRENCHES

- The RIDGID Basin Wrench is an ideal tool for use in tight spaces and under sink applications.
- Spring-loaded jaws of forged alloy steel provide fast, one-hand ratcheting.
- Tension plug holds head in any position up to 90° angle.
- Telescopic shanks on Models 1017 and 1019 quickly adjust for lengths from 10" to 17".

	Catalog No.	Model No.	Description	Nom. Length		Pipe Capacity		Weight		Std.
				in	mm	in	mm	lb	kg	Pack
	31175	1017	Talagagaina Dagin	- 10 - 17 - 240 -	240 425	3/8 - 1 1/4	10 - 32	. 2	0.9	-1
	31180	1019	· Telescoping Basin		240 - 423	1 1/4 - 2 1/2	32 - 65			' '