

MODEL **KW-3800 proXGL & 3800proXG**

1" N-TYPE WRENCH

*Durability has been improved by 20%
compared to previous model KW-3800pro*

KW-3800proXGL



KW-3800proXG



Advantageous Wrench

- Compact & Light
- Hammer - Less Structure
- Low Vibration & Low Noise
- Stable Stroke
- Well - Suited for Assembly Works / Construction works and Tire Changing / U-Bolt Setting Works.

**KUKEN original *N-TYPE* clutch structure resolves
all weakness of conventional impact wrenches.**

SPECIFICATIONS : (Performance figures are at 0.62 MPa(Pe) / 90 P.S.I. air pressure.)

Drive Size	25.4 mm	...	1 "
Capacity of Bolt Size	38.0 mm	...	1-1/2 "
Free Speed	4,500 r.p.m.		
Length (without socket) 3800proXG	335.0 mm	...	13-1/4 "
Length (without socket) 3800proXGL	467.0 mm	...	18-7/16 "
Weight (without socket) 3800proXG	7.0 kg	...	15.4 lbs
Weight (without socket) 3800proXGL	7.4 kg	...	16.3 lbs
Air Consumption	0.63 m ³ /min	...	22.2 c.f.m.
Hose Size	9.5 mm	...	3/8 "
Air Pressure	0.62 MPa	...	90 P.S.I.



KUKEN CO., LTD.

3-6-15 Nonoue, Habikino-shi, Osaka 583-0871, Japan

Tel : +81-72-953-3346 Fax : +81-72-942-8286

Web : www.kuken.co.jp/english E-mail : export1@kuken.co.jp



CAT. No. 300913-3800PX