

FASTENING TOOL

IMPACT WRENCH (N-TYPE)

KUKEN ORIGINAL CLUTCH



■ 1-1/2" (38mm) SQ.DR. KW-5000G

Drive Size	1-1/2 in.	38.0 mm
Bolt Capacity	2 in.	50.0 mm
Free Speed	3,000 r.p.m.	
Impact Per Min.	600 i.p.m.	
Recommended Torque	740-2,520 ft-lb	1,000-3,400 Nm
Maximum Torque	2,590 ft-lb	3,500 Nm
Length (w/o socket)	17-3/8 in.	440.0 mm
Weight (w/o socket)	35.2 lbs.	16.0 kg
Air Consumption (normal)	28.9 c.f.m.	0.82 m³/min.
Hose Size	1/2 in.	12.7 mm
Anvil Length	2-3/16 in.	54.0 mm

Choice of Inside/Outside Trigger Handle.



*Performance figures are at 0.62MPa(Pe) (90P.S.I.) air pressure.

■ 1" (25.4mm) SQ.DR. KW-3800proXG

Drive Size	1 in.	25.4 mm
Bolt Capacity	1-1/2 in.	38.0 mm
Free Speed	4,500 r.p.m.	
Recommended Torque	220-1,010 ft-lb	300-1,370 Nm
Maximum Torque	1,330 ft-lb	1,800 Nm
Length (w/o socket)	13-1/4 in.	335.0 mm
Weight (w/o socket)	15.4 lbs.	7.0 kg
Air Consumption (normal)	22.2 c.f.m.	0.63 m³/min
Hose Size	3/8 in.	9.5 mm

Choice of Inside/Outside Trigger Handle.



*Performance figures are at 0.62MPa(Pe) (90P.S.I.) air pressure.

■ 1" (25.4mm) SQ.DR. KW-3800proXGL

Drive Size	1 in.	25.4 mm
Bolt Capacity	1-1/2 in.	38.0 mm
Free Speed	4,500 r.p.m.	
Recommended Torque	220-1,010 ft-lb	300-1,370 Nm
Maximum Torque	1,330 ft-lb	1,800 Nm
Length (w/o socket)	19-15/16 in.	506.0 mm
Weight (w/o socket)	17.4 lbs.	7.9 kg
Air Consumption (normal)	22.2 c.f.m.	0.63 m³/min
Hose Size	3/8 in.	9.5 mm

Choice of Inside/Outside Trigger Handle.



*Performance figures are at 0.62MPa(Pe) (90P.S.I.) air pressure.

■ 1" (25.4mm) SQ.DR. KW-3800P

Drive Size	1 in.	25.4 mm
Bolt Capacity	1-1/2 in.	38.0 mm
Free Speed	3,700 r.p.m.	
Impact Per Min.	700 i.p.m.	
Recommended Torque	220-1,010 ft-lb	300-1,370 Nm
Maximum Torque	1,330 ft-lb	1,800 Nm
Length (w/o socket)	10-1/16 in.	255.0 mm
Weight (w/o socket)	16.3 lbs.	7.4 kg
Air Consumption (normal)	21.2 c.f.m.	0.60 m³/min
Hose Size	3/8 in.	9.5 mm
Anvil Length (KW-3800P)	1-5/16 in.	33.0 mm
Anvil Length (KW-3800P-6)	4-3/4 in.	120.0 mm



*Performance figures are at 0.62MPa(Pe) (90P.S.I.) air pressure.

■ 1" (25.4mm) SQ.DR. KW-4500P

Drive Size	1 in.	25.4 mm
Bolt Capacity	1-3/4 in.	45.0 mm
Free Speed	3,700 r.p.m.	
Impact Per Min.	700 i.p.m.	
Recommended Torque	740-1,810 ft-lb	1,000-2,450 Nm
Maximum Torque	2,040 ft-lb	2,750 Nm
Length (w/o socket)	10-11/16 in.	270.0 mm
Weight (w/o socket)	22.7 lbs.	10.3 kg
Air Consumption (normal)	27.5 c.f.m.	0.78 m³/min
Hose Size	1/2 in.	12.7 mm
Anvil Length (KW-4500P)	1-1/2 in.	37.0 mm
Anvil Length (KW-4500P-6)	4-3/4 in.	120.0 mm



*Performance figures are at 0.62MPa(Pe) (90P.S.I.) air pressure.

■ 1" (25.4mm) SQ.DR. KW-4500G

Drive Size	1 in.	25.4 mm
Bolt Capacity	1-3/4 in.	45.0 mm
Free Speed	3,700 r.p.m.	
Impact Per Min.	700 i.p.m.	
Recommended Torque	740-1,810 ft-lb	1,000-2,450 Nm
Maximum Torque	2,040 ft-lb	2,750 Nm
Length (w/o socket)	14-7/16 in.	366.0 mm
Weight (w/o socket)	23.5 lbs.	10.7 kg
Air Consumption (normal)	26.5 c.f.m.	0.75 m³/min
Hose Size	1/2 in.	12.7 mm
Anvil Length	1-1/2 in.	37.0 mm

Choice of Inside/Outside Trigger Handle.



*Performance figures are at 0.62MPa(Pe) (90P.S.I.) air pressure.

■ 1" (25.4mm) SQ.DR. KW-4500GL

Drive Size	1 in.	25.4 mm
Bolt Capacity	1-3/4 in.	45.0 mm
Free Speed	3,700 r.p.m.	
Impact Per Min.	700 i.p.m.	
Recommended Torque	740-1,810 ft-lb	1,000-2,450 Nm
Maximum Torque	2,040 ft-lb	2,750 Nm
Length (w/o socket)	21 in.	532.0 mm
Weight (w/o socket)	25.5 lbs.	11.6 kg
Air Consumption (normal)	26.5 c.f.m.	0.75 m³/min
Hose Size	1/2 in.	12.7 mm
Anvil Length	8 in.	203.0 mm

Choice of Inside/Outside Trigger Handle.



*Performance figures are at 0.62MPa(Pe) (90P.S.I.) air pressure.