

FASTENING TOOL

IMPACT WRENCH

Pin Clutch



Choice of Inside/
Outside Trigger Handle.

■ SPLINE DR. HEAVY DUTY IMPACT WRENCH

KW-45FS

Drive Size	#5 Spline	
Bolt Capacity	1-5/16 in.**	33.0 mm**
Free Speed	2,800 r.p.m.	
Impact Per Min.	550 i.p.m.	
Recommended Torque	580-2,150 ft-lb	780-2,900 Nm
Maximum Torque	2,370 ft-lb	3,200 Nm
Length (w/o socket)	18-11/16 in.	474.0 mm
Weight (w/o socket)	38.7 lbs.	17.6 kg
Air Consumption (normal)	30.0 c.f.m.	0.85 m ³ /min
Hose Size	1/2 in.	12.7 mm
Anvil Length	2-3/16 in.	54.0 mm

**Designed for high tension bolt.

*Performance figures are at 0.62MPa(Pe)(90P.S.I.)air pressure.

Pin Clutch



Choice of Inside/
Outside Trigger Handle.

■ 1" (25.4mm) HEAVY DUTY IMPACT WRENCH

KW-45F-1

Drive Size	1 in.	25.4 mm
Bolt Capacity	1-5/16 in.**	33.0 mm**
Free Speed	2,800 r.p.m.	
Impact Per Min.	550 i.p.m.	
Recommended Torque	580-2,150 ft-lb	780-2,900 Nm
Maximum Torque	2,370 ft-lb	3,200 Nm
Length (w/o socket)	18-11/16 in.	474.0 mm
Weight (w/o socket)	37.8 lbs.	17.2 kg
Air Consumption (normal)	30.0 c.f.m.	0.85 m ³ /min
Hose Size	1/2 in.	12.7 mm
Anvil Length	2-3/16 in.	54.0 mm

**Designed for high tension bolt.

*Performance figures are at 0.62MPa(Pe)(90P.S.I.)air pressure.

Pin Clutch



Choice of Inside/
Outside Trigger Handle.

■ 1-1/2" (38.0mm) HEAVY DUTY IMPACT WRENCH

KW-45F

Drive Size	1-1/2 in.	38.0 mm
Bolt Capacity	1-5/16 in.**	33.0 mm**
Free Speed	2,800 r.p.m.	
Impact Per Min.	550 i.p.m.	
Recommended Torque	580-2,150 ft-lb	780-2,900 Nm
Maximum Torque	2,370 ft-lb	3,200 Nm
Length (w/o socket)	18-11/16 in.	474.0 mm
Weight (w/o socket)	37.8 lbs.	17.2 kg
Air Consumption (normal)	30.0 c.f.m.	0.85 m ³ /min
Hose Size	1/2 in.	12.7 mm
Anvil Length	2-3/16 in.	54.0 mm

**Designed for high tension bolt.

*Performance figures are at 0.62MPa(Pe)(90P.S.I.)air pressure.

Pin Clutch



Choice of Inside/
Outside Trigger Handle.

■ 1-1/2" (38.0mm) HEAVY DUTY IMPACT WRENCH

KW-75F

Drive Size	1-1/2 in.	38.0 mm
Bolt Capacity	2 in.**	50.0 mm**
Free Speed	2,000 r.p.m.	
Impact Per Min.	350 i.p.m.	
Recommended Torque	1,110-4,460 ft-lb	1,500-6,300 Nm
Maximum Torque	4,460 ft-lb	6,300 Nm
Length (w/o socket)	23-7/8 in.	605.0 mm
Weight (w/o socket)	83.8 lbs.	38.1 kg
Air Consumption (normal)	31.8 c.f.m.	0.90 m ³ /min
Hose Size	3/4 in.	19.0 mm
Anvil Length	2-1/16 in.	51.0 mm

**Designed for high tension bolt.

*Performance figures are at 0.62MPa (Pe)(90P.S.I.)air pressure.