

SERVICE JACK(Manual type)

Used at automotive workshops and gas stations the world over.
All models are equipped with safety valve.

SJ-20S-3
2ton



SJ-20LL-2
2ton
Service Jack(manual type)
Easier operation by
installing foot-pedal



SJ-30H
3ton



SERVICE JACK(Air type)

Equipped with an air pump that increases working efficiency.
Easy operation by push-button, especially for use in narrow place.

ASJ-20ML
2ton

Service Jack,low profile
(available for air and manual type)
Possible for lift 2 ton load
from min height.



ASJ-30ML
3ton

Service Jack,low profile
(available for air and manual type)
Possible for lift 3 ton load from
min height.



ASJ-18M-2S
1.8ton

Service Jack,low profile
(available for air and manual type)
Height can be adjusted by installing
adjustable screw which is the best to
avoid damage of lower part of a car.



■ Option (1.5ton~2ton)
With Nylon wheels,(Low-Noise)



■ Option (3ton,2ton)
Urethane wheels,(Low-Noise)



AIR HYDRAULIC TRUCK JACK

Compact but Powerful · Ideal for heavy duty truck and bus. Rubber wheels
for easy maneuverability.

ZATJ-22S-4
20ton



APJ-250
25ton



AIR HYDRAULIC PORTABLE JACK
Light weight and compact
design for easy portability.

ATJ-350
35ton



ATJ-200DL-2
20ton



SERVICE JACK SPECIFICATIONS

Spec.	Capacity	Min. Height	Lift.	Max. Height	Height of Frame	Weight	Remarks
Model	(ton)	(mm)	(mm)	(mm)	(mm)	(kg)	
SJ-15H-3	1.5	113	360	473	150	33	
SJ-20S-3	2	113	360	473	150	33	
SJ-20L-2	2	116	360	476	160	45	
SJ-20LL-2 with a pedal	2	98	410	508	120	57	Low profile
SJ-30H with a pedal	3	126	480	606	190	65	
SJ-30LL with a pedal	3	98	515	613	135	80	Low profile
SJ-50H with a pedal	5	150	410	560	200	85	
SJ-100H with a pedal	10	160	400	560	250	135	

AIR SERVICE JACK SPECIFICATIONS

Spec.	Capacity	Min. Height	Lift.	Max. Height	Height of Frame	Weight	Remarks
Model	(ton)	(mm)	(mm)	(mm)	(mm)	(kg)	
ASJ-18M-2S	1.8	104	505	609	120	61	Low profile
ASJ-20ML	2	98	410	508	120	59	Low profile
ASJ-30M with a pedal	3	126	480	606	190	75	
ASJ-30ML with a pedal	3	98	515	613	135	90	Low profile
ASJ-50M with a pedal	5	150	410	560	200	93	
ASJ-50ML with a pedal	5	115	410	525	150	102	Low profile
ASJ-80ML with a pedal	8	115	445	560	180	140	Low profile
ASJ-100M with a pedal	10	160	400	560	250	140	
※ASJ-150-2	15	175	475	650	230	235	

※Only for air operation

HYDRAULIC PANTAGRAPH JACK

● For tires replacement · for putting on and taking off a chain.



MSJ-850
850kg

HYDRAULIC PANTAGRAPH JACK SPECIFICATIONS

Spec.	Capacity	Min. Height	Lift.	Max. Height	Weight
Model	(kg)	(mm)	(mm)	(mm)	(kg)
MSJ-850	850	121	260	381	5.9

AIR HYDRAULIC TRUCK JACK SPECIFICATIONS

Spec.	Capacity	Min. Height	Lift.	Extension Screw Height	Max. Height	Weight	Remarks
Model	(ton)	(mm)	(mm)	(mm)	(mm)	(kg)	
ZATJ-22S-4※	20	198	105	95	398	33	
ATJ-200DL-2	20	143	100	-	243	44	Low profile
ATJ-200	20	210	105	90	405	40	
ATJ-250	25	210	105	90	405	43	
ATJ-350	35	210	100	70	380	45	
ATJ-350L	35	170	80	50	300	43	Low profile
APJ-200-2※	20	210	120	105	435	14	
APJ-250※	25	230	120	105	455	18.5	

※The adapter of ZATJ-22S-4 and APJ-200,250 are option.
The small and big adapter are standard equipment for other ※mark.