



HT-150 SAFETY SYSTEM INSIDE

- Flip top style head, rotates 180°
- With safety valve inside to avoid overload

Technical data	
Crimping range:	Cu 4-150mm ²
Crimping force:	35kN
Length:	215mm
Crimping type:	Hexagon Crimping
Accessories:	
Crimping dies:	4,6,8,10,16,25,35,50,70,95,120,150mm ²



THS-150

- Flip top style head, rotates 180°
- With safety valve inside to avoid overload

Technical data	
Crimping range:	Cu10-150mm ²
Crimping force:	60kN
Crimping dies:	10-16,25-35,50-70,95-120,150mm ²



CYO-510B SAFETY SYSTEM INSIDE

- Two stage hydraulic system with fast feed and power stroke, With Safety valve, twist the active handle to release the pressure

Technical data	
Crimping force:	126kN
Crimping range:	Cu 50-400mm ²
Stroke:	38mm
Oil capacity:	145cc
Accessories:	
Crimping dies:	50,70,95,120,150,185,240,300,400mm ²



CYO-400C FLIP TOP STYLE HEAD

- Two stage hydraulic system with fast feed and power stroke

Technical data	
Crimping force:	126kN
Crimping range:	Cu 16-400mm ²
Stroke:	25mm
Oil capacity:	145cc
Accessories:	
Crimping dies:	16,25,35,50,70,95,120,150,185,240,300,400mm ²



CYO-6B Up to 240mm²

- Quad-point indent crimping feature, no die required
 - The head can rotate 350°
 - With Safety valve, twist the active handle to release the pressure
- Suitable for crimping tubular cable lugs and connectors "standard type" and fine and superline stranded conductors to 240mm²

Technical data	
Crimping range:	Cu10-240mm ²
Crimping force:	60kN
Stroke:	35mm



CYO-430 SAFETY SYSTEM INSIDE

- Two stage hydraulic system with fast feed and power stroke, With Safety valve, twist the active handle to release the pressure

Technical data	
Crimping force:	116kN
Crimping range:	Cu50-400mm ²
Stroke:	30mm
Oil capacity:	145cc
Accessories:	
Crimping dies:	50,70,95,120,150,185,240,300,400mm ²



YQK-70

- Single stage plunger pump, simple structure, reliable performance, interchangeable dies for different size

Technical data	
Crimping range:	Cu 4-70mm ²
Crimping force:	45kN
Stroke:	11mm
Crimping type:	Hexagon Crimping
Accessories:	
Crimping dies:	4, 6, 8, 10, 16, 25, 35, 50, 70mm ²
Sealing O-ring:	One Set



YYQ-120A

- Two stage hydraulic system with fast feed and power stroke

Technical data	
Crimping range:	Cu10-120mm ²
Crimping force:	60kN
Stroke:	13mm
Crimping type:	Hexagon Crimping
Accessories:	
Crimping dies:	10,16,25,35,50,70,95,120mm ²
Sealing O-ring:	One Set