

Impact Accessory

8260

- Extension bar
- DIN 3121



8260




8260P

KT NO.	Overall Length Inch	mm		
8260-07	7	175	1400	1 / 12
8260-10	10	250	1932	1 / 12
8260-13	13	330	2458	1 / 8
8260-07P	7	175	1400	1 / 12
8260-10P	10	250	1932	1 / 12
8260-13P	13	330	2458	1 / 8

8797

- Universal joint
- DIN 3121



8797P

1"



8797



8797P

KT NO.	Overall Length Inch	mm	D mm		
8797	5	125	60	1491	1 / 18
8797P	5	125	60	1491	1 / 18

8866

- Adapter
- Convert to 3/4" drive
- 8866 → Max. torque : 1412 N·m
- DIN 3121



8866

8866P

1"



8866P

KT NO.	Spec.		
8866	1" F x 3/4" M	606	4 / 32
8866P	1" F x 3/4" M	606	4 / 32

8869

- Adapter
- Convert to 1-1/2" drive
- DIN 3121



8869

8869P

1"



8869P

KT NO.	Spec.		
8869	1" F x 1-1/2" M	941	1 / 24
8869P	1" F x 1-1/2" M	941	1 / 24

90405


- Locking ring
- High tensile rubber material

90605

- Locking pin
- Chrome vanadium steel
- DIN 3129



90605
90606



90405
90406

KT NO. Type ϕ d / l Applied to socket sizes

90405	ring	5.5	44	8535M (19~70mm) 8535S (3/4"~2-3/4") 8435M (24~60mm) 8435S (15/16"~2-1/4") 8835M (24~60mm) 8514M, 8514S, 8534M, 806519M 8260, 8797, 8866, 8869
90605	pin	5.0	45	
90406	ring	10	75	8535M (71~90mm) 8535S (2-13/16"~3-1/2")
90606	pin	5.0	75	