

Grease Pump Kit

TMK1-GP3

Trolley mounted kits are ideal for use in workshops, garages, shop floors providing complete portability for everyday lubrication needs



KIT INCLUDES

A	50:1 Air Operated Grease Pump
B	Grease Control Valve With Z swivel for trouble free dispensing
C	Connecting Hose 84" x 1/4" I.D. (2m x 6.5 mm I.D.) - SAE R2
D	Steel Drum Cover 24-1/2" (612 mm) Prevents contamination of grease and keeps pump in vertical position
E	Rubber Lined Follower Plate O.D. Steel End: 21-5/8" (550 mm) O.D. Plate: 23-11/16" (602 mm) I.D. Grommet: 1-3/16" (29.5 mm)
F	Drum Cart Manufactured from thick steel sheet in powder coated finish Front Wheels: 10" (250 mm) wide Rear castors with toe lock 5" nylon



WETTED COMPONENTS

Steel, Brass, Aluminium, Polyurethane & Nitrile Rubber

RECOMMENDED USE

With light and self collapsing grease up to NLGI No. 2

ORDERING INFORMATION

CAT NR.	ORD NR.	THREADS	BOX QTY.
TMK1/GP3/B/BSP	45860	1/8" BSPT	1
TMK1/GP3/B/N	45865	1/8" NPT	1

SPECIFICATIONS

WORKING PRESSURE	30-150 PSI	2-10 BAR
MAX. AIR PRESSURE	150 PSI	10 BAR
MAX. OUTLET PRESSURE	7,500 PSI	500 BAR
AIR INLET CONNECTION	1/4" (F)	
PUMP OUTLET	1/4" (F)	
AIR CONSUMPTION	72 GPM	270 LPM
NOISE LEVEL	85 db	
GREASE OUTPUT (MAX.)	2.42 LBS./MIN.	1.1 KG/MIN.
FOR USE WITH	400 LBS. DRUMS	180 KG DRUMS