


265

Industrial torque wrench 3/4"



- robust construction gives accurate results, to +/-4%, even in arduous working conditions.
- every wrench supplied with a calibration certificate according to ISO 9000:2000
- the large break angle improves accuracy by reducing the possibility of over torquing
- Cam control of the mechanism gives a controlled break which will not throw the operator off balance
- Torque application: both way, but always apply in direction specified on torque wrench handle
- dual scaled, N.m and lbf.ft
- made according to standard ISO 6789

Usage:

- agricultural equipment
- building sector
- heavy industry
- larger construction machinery
- shipbuilding industry
- aircraft industry
- Do not use torque wrench for untightening!


Important!

- Tool must be used with equal pulls and in accordance with the instructions in the manual.
- Torque tightens only in the direction showed on the key sticker! Sticker shows the proper direction of tightening!
- The default calibration interval of the torque wrench is 12 months or 5.000 measurements from the date of end user purchase.
- ALWAYS set the measuring mechanism to starting point, at the end of work.
- When the requested torque is reached, please do not tight any more.
- Torque wrench can be damaged, if manual instructions are not considered.



267A

Pre-set torque wrenches for cars



- material: premium chrome vanadium steel
- guaranteed to meet ISO 6789, ANSI 107.14M and U.S. Fed GGG-W-686D
- torque is preset
- easy to use and calibrate
- factory calibrated for accuracy to within +/-4%

Important!

- Do not use torque wrench for untightening!
- Torque tightens only in the direction showed on the key sticker! Sticker shows the proper direction of tightening!
- The default calibration interval of the torque wrench is 12 months or 5.000 measurements from the date of end user purchase.
- When the requested torque is reached, please do not tight any more.
- Torque wrench can be damaged, if manual instructions are not considered.

Barcode	Scale 1	Scale 2	Color	L	Weight	Scale	Qty
618915	90	66.4	black	400	1340	IS	1
618916	100	73.7	yellow	400	1335	IS	1
618917	110	81.1	gray	400	1335	IS	1
618918	120	88.5	red	400	1335	IS	1
618919	130	95.9	blue	400	1335	IS	1

Barcode	Scale 1	Scale 2	L	Weight	Scale	Qty	
616801	3/4"	150 - 700	100 - 500	1090	8500	1S	1
616802	3/4"	200 - 800	150 - 600	1140	9000	1S	1
616803	3/4"	300 - 1000	200 - 750	1470	11000	1S	1

